

**Scentinel® E Gas Odorant**

Version 1.5

Revision Date 2013-07-16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Trade name : Scentinel® E Gas Odorant
Material : 1106808, 1086435, 1086434, 1095112, 1079767, 1064505,
1098464, 1098226, 1024677, 1024673, 1034741, 1024674,
1024676, 1024678, 1024780, 1024782, 1024781, 1024778,
1024783, 1036153, 1024779, 1024675, 1105014

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

North America: CHEMTREC 800.424.9300 or 703.527.3887

Asia: +800 CHEMCALL (+800 2436 2255)

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
E-mail address : MSDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Emergency Overview****Physical state:** Liquid **Color:** Clear **Odor:** Repulsive

OSHA Hazards : Flammable Liquid, Harmful by ingestion., Harmful by skin
absorption., Moderate skin irritant, Moderate eye irritant

GHS Classification





: Flammable liquids, Category 2
Skin sensitization, Sub-category 1B
Aspiration hazard, Category 2
Acute aquatic toxicity, Category 1
Chronic aquatic toxicity, Category 2

GHS-Labeling

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

Symbol(s)	:	   
Signal Word	:	Danger
Hazard Statements	:	<p>H225: Highly flammable liquid and vapor. H305: May be harmful if swallowed and enters airways. H317: May cause an allergic skin reaction. H400: Very toxic to aquatic life. H411: Toxic to aquatic life with long lasting effects.</p>
Precautionary Statements	:	<p>Prevention: P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P233: Keep container tightly closed. P240: Ground/bond container and receiving equipment. P241: Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242: Use only non-sparking tools. P243: Take precautionary measures against static discharge. P261: Avoid breathing dust/fume/gas/mist/vapors/spray. P272: Contaminated work clothing should not be allowed out of the workplace. P273: Avoid release to the environment. P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>Response: P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. P303 + P361 + P353: IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P321: Specific treatment (see supplemental first aid instructions on this label). P331: Do NOT induce vomiting. P333 + P313: If skin irritation or rash occurs: Get medical advice/ attention. P363: Wash contaminated clothing before reuse. P370 + P378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. P391: Collect spillage.</p> <p>Storage: P403 + P235: Store in a well-ventilated place. Keep cool. P405: Store locked up.</p> <p>Disposal: P501: Dispose of contents/ container to an approved waste disposal plant.</p>
Carcinogenicity:		
IARC		No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
NTP		No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
ACGIH		No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

by ACGIH.

SECTION 3: Composition/information on ingredients

Synonyms : Mercaptan Mixture
Gas Odorant

Molecular formula : Mixture

Component	CAS-No.	Weight %
t-Butyl Mercaptan	75-66-1	75 - 80
Isopropyl Mercaptan	75-33-2	13 - 18
n-Propyl Mercaptan	107-03-9	3 - 8

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.

If inhaled : Move to fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point : -18 °C (0 °F)
estimated

Autoignition temperature : 200 °C (392 °F)

Suitable extinguishing media : Dry chemical. Carbon dioxide (CO₂). Alcohol-resistant foam.

Unsuitable extinguishing media : High volume water jet.

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

- | | | |
|--|---|--|
| Special protective equipment for fire-fighters | : | Wear self contained breathing apparatus for fire fighting if necessary. |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers. |
| Fire and explosion protection | : | Do not spray on an open flame or any other incandescent material. Use only explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition. |
| Hazardous decomposition products | : | Carbon oxides. Sulfur oxides. |

SECTION 6: Accidental release measures

- | | | |
|---------------------------|---|---|
| Personal precautions | : | Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. |
| Environmental precautions | : | Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods for cleaning up | : | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |

SECTION 7: Handling and storage**Handling**

- | | | |
|---|---|--|
| Advice on safe handling | : | Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations. Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. |
| Advice on protection against fire and explosion | : | Do not spray on an open flame or any other incandescent material. Use only explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open |

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Chevron Phillips Chemical Company LP**

Ingredients	Basis	Value	Control parameters	Note
t-Butyl Mercaptan	Manufacturer	TWA	0.5 ppm,	

Personal protective equipment

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as:. Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Physical state : Liquid

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

Color : Clear
Odor : Repulsive

Safety data

Flash point : -18 °C (0 °F)
estimated

Lower explosion limit : 1.4 %(V)

Upper explosion limit : 12.5 %(V)

Oxidizing properties : no

Autoignition temperature : 200 °C (392 °F)

Molecular formula : Mixture

Molecular Weight : Not applicable

pH : Not applicable

Pour point : No data available

Boiling point/boiling range : 57 - 60 °C (135 - 140 °F)

Vapor pressure : 7.00 PSI
at 38 °C (100 °F)

Relative density : 0.81, 16 °C(61 °F)

Water solubility : Negligible

Partition coefficient: n-
octanol/water : No data available

Viscosity, kinematic : No data available

Relative vapor density : 2
(Air = 1.0)

Evaporation rate : > 1
(N-Butyl Acetate = 1)

Percent volatile : > 99 %

SECTION 10: Stability and reactivity**Possibility of hazardous reactions**

Conditions to avoid : Not applicable.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

Other data : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Scentinel® E Gas Odorant**

Acute oral toxicity : Acute toxicity estimate: 10,366 mg/kg
Method: Calculation method

Acute inhalation toxicity

t-Butyl Mercaptan : LC50: 26643 ppm
Exposure time: 4 h
Species: rat
Sex: male and female
Test atmosphere: vapor
Method: OECD Test Guideline 403

LC50: 22200 ppm
Exposure time: 4 h
Species: rat
Sex: male
Test atmosphere: vapor
Method: OECD Test Guideline 403

LC50: 16500 ppm
Exposure time: 4 h
Species: mouse
Sex: male
Test atmosphere: vapor
Method: OECD Test Guideline 403

Isopropyl Mercaptan LC50: > 32.24 mg/l
Exposure time: 4 h
Species: rat
Sex: male and female
Test atmosphere: vapor
Method: OECD Test Guideline 403
Test substance: yes
An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

n-Propyl Mercaptan LC50: > 25.5 mg/l
Exposure time: 4 h
Species: rat
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.

Acute dermal toxicity

t-Butyl Mercaptan : LD50: > 2,000 mg/kg
Species: rabbit

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

Isopropyl Mercaptan LD50: > 2,000 mg/kg
 Species: rat
 Method: No information available.
 see user defined free text

n-Propyl Mercaptan LD50: > 1,682 mg/kg
 Species: rabbit
 Sex: male and female
 Method: OECD Test Guideline 402

**Scentinel® E Gas Odorant
 Skin irritation** : May cause skin irritation and/or dermatitis.

**Scentinel® E Gas Odorant
 Eye irritation** : May cause irreversible eye damage.

**Scentinel® E Gas Odorant
 Sensitization** : Causes sensitization.

Repeated dose toxicity

t-Butyl Mercaptan : Species: rat, Male and female
 Sex: Male and female
 Application Route: Inhalation
 Dose: 9, 97, 196 ppm
 Exposure time: 13 wks
 Number of exposures: 6 hrs/d, 5 d/wk
 NOEL: > 196 ppm

Species: rat, Male and female
 Sex: Male and female
 Application Route: oral gavage
 Dose: 10, 50, 200 mg/kg bw/day
 Exposure time: 42-53 days
 Number of exposures: Daily
 NOEL: 50 mg/kg bw/day
 Lowest observable effect level: 200 mg/kg bw/day
 Method: OECD Guideline 422

Species: rat, Male and female
 Sex: Male and female
 Application Route: Inhalation
 Dose: 25.1, 99.6, 403.4 ppm
 Exposure time: 13 wks
 Number of exposures: 6 hrs/d, 5 d/wk
 NOEL: 99.6 ppm
 Lowest observable effect level: 403.4 ppm
 Method: OECD Guideline 413
 Target Organs: Liver, Kidney, Blood, Upper respiratory tract

Reproductive toxicity

t-Butyl Mercaptan : Species: rat
 Sex: male and female
 Application Route: oral gavage
 Dose: 10, 50, 200 mg/kg bw/day
 Number of exposures: Daily
 Test period: 42 -53 days

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

Method: OECD Guideline 422
 NOAEL Parent: 200 mg/kg bw/day
 NOAEL F1: 50 mg/kg bw/day
 No adverse effects expected

Teratogenicity

t-Butyl Mercaptan

: Species: mouse
 Application Route: Inhalation
 Dose: 11, 99, 195 ppm
 Exposure time: GD 6-16
 Number of exposures: 6 hrs/d
 NOAEL Teratogenicity: > = 195 ppm
 NOAEL Maternal: > = 195 ppm

Species: rat
 Application Route: Inhalation
 Dose: 11, 99, 195 ppm
 Exposure time: GD6-19
 Number of exposures: 6 hrs/d
 NOAEL Teratogenicity: > =195 ppm
 NOAEL Maternal: > = 195 ppm

Species: rat
 Application Route: oral gavage
 Dose: 10, 50, 200 mg/kg bw/day
 Exposure time: 42-53 days
 Number of exposures: Daily
 NOAEL Teratogenicity: 200 mg/kg bw /day

**Scentinel® E Gas Odorant
Aspiration toxicity**

: May be harmful if swallowed and enters airways.
 Substances known to cause human aspiration toxicity hazards
 or to be regarded as if they cause human aspiration toxicity
 hazard.

CMR effects

t-Butyl Mercaptan

: Carcinogenicity: Not available
 Mutagenicity: Did not show mutagenic effects in animal
 experiments.
 Teratogenicity: Did not show teratogenic effects in animal
 experiments.
 Reproductive toxicity: No toxicity to reproduction

**Scentinel® E Gas Odorant
Further information**

: Concentrations substantially above the TLV value may cause
 narcotic effects. Symptoms of overexposure may be
 headache, dizziness, tiredness, nausea and vomiting.
 Solvents may degrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

t-Butyl Mercaptan

: LC50: 34 mg/l
 Exposure time: 96 h

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

	Species: <i>Oncorhynchus mykiss</i> (rainbow trout) semi-static test Method: OECD Test Guideline 203
Isopropyl Mercaptan	LC50: 34 mg/l Exposure time: 96 h semi-static test Analytical monitoring: yes Method: OECD Test Guideline 203 Information given is based on data obtained from similar substances.
n-Propyl Mercaptan	LC50: 1.3 mg/l Exposure time: 96 h Species: <i>Pimephales promelas</i> (fathead minnow) Analytical monitoring: yes Test substance: yes Method: OECD Test Guideline 203 Toxic to aquatic organisms.

Toxicity to daphnia and other aquatic invertebrates

t-Butyl Mercaptan	: EC50: 6.7 mg/l Exposure time: 48 h Species: <i>Daphnia magna</i> (Water flea) static test Method: OECD Test Guideline 202
Isopropyl Mercaptan	EC50: 0.25 - 0.5 mg/l Exposure time: 48 h Species: <i>Daphnia magna</i> (Water flea) static test Test substance: yes Method: OECD Test Guideline 202
n-Propyl Mercaptan	0.07 mg/l Exposure time: 48 h Species: <i>Daphnia magna</i> (Water flea) Analytical monitoring: yes Test substance: yes Method: OECD Test Guideline 202 Very toxic to aquatic organisms.

Toxicity to algae

t-Butyl Mercaptan	: EC50: 24 mg/l Exposure time: 72 h Species: <i>Pseudokirchneriella subcapitata</i> (green algae) Method: OECD Test Guideline 201
propane-2-thiol	: 1
propane-1-thiol	10

Elimination information (persistence and degradability)

Bioaccumulation

t-Butyl Mercaptan	: Bioconcentration factor (BCF): 12 Bioaccumulation is unlikely.
-------------------	---

Biodegradability	: Expected to be biodegradable
------------------	--------------------------------

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

Results of PBT assessment

- t-Butyl Mercaptan : Non-classified PBT substance, Non-classified vPvB substance
- Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this MSDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

- Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the MSDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II, MARINE POLLUTANT

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II, (-18 °C), MARINE POLLUTANT, (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II, ENVIRONMENTALLY HAZARDOUS

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN3336, MERCAPTANS, LIQUID, FLAMMABLE, N.O.S., (TERTIARY BUTYL MERCAPTAN, ISOPROPYL MERCAPTAN), 3, II, ENVIRONMENTALLY HAZARDOUS

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation**

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard

EPCRA - EMERGENCY PLANNING COMMUNITY RIGHT - TO - KNOW

CERCLA Reportable Quantity : This material does not contain any components with a CERCLA RQ.

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

SARA 313 Ingredients : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

US State Regulations**Massachusetts Right To Know**

: n-Propyl Mercaptan - 107-03-9
 t-Butyl Mercaptan - 75-66-1
 Isopropyl Mercaptan - 75-33-2

Pennsylvania Right To Know

: t-Butyl Mercaptan - 75-66-1

New Jersey Right To Know

: n-Propyl Mercaptan - 107-03-9
 t-Butyl Mercaptan - 75-66-1
 Isopropyl Mercaptan - 75-33-2

**California Prop. 65
Ingredients**

: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Notification status

Europe REACH : On the inventory, or in compliance with the inventory
 United States of America US.TSCA : On the inventory, or in compliance with the inventory
 Canada DSL : On the inventory, or in compliance with the inventory
 Australia AICS : On the inventory, or in compliance with the inventory
 New Zealand NZIoC : On the inventory, or in compliance with the inventory
 Japan ENCS : On the inventory, or in compliance with the inventory
 Korea KECI : On the inventory, or in compliance with the inventory
 Philippines PICCS : On the inventory, or in compliance with the inventory

Scentinel® E Gas Odorant


Version 1.5

Revision Date 2013-07-16

China IECSC : On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

**Further information**

Legacy MSDS Number : 93850

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this MSDS pertains only to the product as shipped.

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research	TLV	Threshold Limit Value

Scentinel® E Gas Odorant

Version 1.5

Revision Date 2013-07-16

	on Cancer		
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		